

Dress up your Luxury Project

Prodotti per Legatoria - Cartotecnica - Arti Grafiche
Saldatori Plastici Campionaristi Scatolifici

Registered Office: 20138 Milan - Via M.F. Quintiliano, 2/4
Administrative Offices: 20138 Milan - Via Salomone, 43
T. +39 (02) 58.012.660 - 58.011.069 F. +39 (02) 50.633.14
Share Capital € 100.000 i.v. - REA MI 1252539
VAT No. 08837680159

www.cavalliniring.it - vendite@cavalliniring.it
Certified Email PEC: cavallinisrl@ticertifica.it

"Since 1987... Quality & Service"

BLACK FIBRONE

PRODUCT DESCRIPTION

Fibrone is highly resistant to bending and has a high density. It is used for ring binders, boxes and in the automotive industry. Available in the standard size 770 × 1040 mm.

TECHNICAL SPECIFICATIONS

Color	black
Thickness	1.0-3.2 mm
Grammage	1000-3200 g/m ²
Tolerances	Specific weight and thickness ± 5 %
Machine format	< 1200 g/m ² : 242 × 308 cm > 1200 g/m ² : 244 × 308 cm

Other formats available on request (there may be differences depending on the specific weight)		
122 × 154 cm LG*	81 × 154 cm LG	61 × 154 cm LG
122 × 102 cm SG*	81 × 102 cm LG	61 × 102 cm LG
122 × 77 cm SG	81 × 77 cm SG	61 × 77 cm LG
122 × 61 cm SG	81 × 61 cm SG	61 × 61 cm

*LG (long grain)
SG (short grain)

PROCESSING

- machine formats
- angled cuts – possible with guillotine and circular shears
- punching – maximum punching size 118 × 82 cm or 122 × 88 cm (depending on format and quantity)
- rounded and beveled corners
- stacking and strapping
- creasing, scoring
- varnishing
- printing: crocodile or marbled effect
- coating: corrosion-resistant and electrically conductive
- embossing: leather effect, hippo, Macro or Matte



Discover our FSC® certified products

Only the products that are identified as such on this document are FSC® certified