

Dress up your Luxury Project

Prodotti per Legatoria - Cartotecnica - Arti Grafiche
Saldatori Plastici Campionaristi Scatolifici

Registered Office: 20138 Milan - Via M.F. Quintiliano, 2/4
Administrative Offices: 20138 Milan - Via Salomone, 43
T. +39 (02) 58.012.660 - 58.011.069 F. +39 (02) 50.633.14
Share Capital € 100.000 i.v. - REA MI 1252539
VAT No. 08837680159

www.cavalliniring.it - vendite@cavalliniring.it
Certified Email PEC: cavallinisrl@ticertifica.it

"Since 1987... Quality & Service"

LYNEL COLLECTION

As the exclusive distributor of this flocked covering material in Italy, Cavallini S.r.l. supplies this product exclusively within the Italian market.

AVAILABLE BACKINGS

Lynel Tann SG: 95 g/m² paper backing
Lynel Tann PVC: 250 µm plastisol backing
Lynel Fur SG: 95 g/m² paper backing
Lynel Fur PVC: 250 µm plastisol backing

TECHNICAL SPECIFICATIONS - LYNEL TANN AND FUR SG

Total Grammage: 230 ± 25 g/m²
Thickness: 0,50 ± 0,05 mm
Roll size: 104cmx100 m

TECHNICAL SPECIFICATIONS - LYNEL TANN AND FUR PVC

Total Grammage: 470 ± 25 g/m²
Thickness: 0,60 ± 0,05 mm
Roll size: 140cmx50 m

ROLL PACKAGING

Roll Size*: 100 m x 104 cm
Core Diameter: 76 mm
Roll Weight: 27 kg

* Except Neige 08, supplied in 50 m rolls. Other roll lengths, widths and sheet formats are available upon request.

RECOMMENDED SHELF LIFE

It is recommended that the material be used within one year of delivery.

GENERAL HOT FOIL STAMPING CONDITIONS

0,5 sec – temperature 120 °C – pressure approximately 200 kg/cm²

ADDITIONAL INFORMATION

Neutral product (does not damage precious metals).
Free from azo compounds and asbestos.
Free from volatile organic compounds (VOCs).
LYNEL SG complies with EN 71-3 (Safety of Toys – Part 3).
Specific colour tolerances apply to each colour.



Discover our FSC® certified products

Only the products that are identified as such on this document are FSC® certified